

**MATLAB BASED MODELING AND SIMULINK PACKAGE FOR DC-DC
BOOST CONVERTOR TO ENHANCE LEARNING PROCESS OF POWER
ELECTRONICS.**

MUHAMMAD MUJTABA ASAD

A project report submitted in partial fulfilment of the requirement for the award of the
Degree of Masters in Technical and Vocational Education

Faculty of Technical and Vocational Education

UNIVERSITI TUN HUSSEIN ONN MALAYSIA

January 2014

DEDICATION

To my beloved grandfather Mr. Haji Banaras Khan (Late), beloved parents, sisters, brothers, friends and lecturers, without your fully support, guidance and advice I might not had this kind of achievement. Thanks for all the supports.

May Allah S.W.T bless you.



PTTA UTM
PERPUSTAKAAN TUNKU TUN AMINAH

ACKNOWLEDGEMENT

Throughout the entire process of development and implementation of the project, I am very fortunate to have a number of wonderful and experienced people who have been giving me assistance and direction towards completing this project.

First and foremost, Thanks to Allah Almighty to grant me all the opportunities in my life and blessing me with the success to complete this degree. I would like to express my utmost and deepest gratitude to my project supervisor, Dr. Razali Bin Hassan for his advice, and persistent guidance when needed throughout the whole academic year. It would have been very difficult to complete this project without the enthusiastic support, insight, and advice given by him.

Subsequently, I would like to thank my parents, Mr & Mrs Muhammad Ejaz Asad, who have inspired and given me immeasurable direction in being an able-minded individual when crafting this study, also I would like to convey my deepest gratitude and thanks to my family, for their support spiritually and financially in order to finish my study. Also, It would have been not possible for me to earn this achievement without the valuable prayers of my grandmothers. Apart from family, It is also important to be grateful to my friends circle for all of their moral support and motivation.

Last but not least, to all my family and friends whom I have not mentioned who have helped me one-way or the other and given me encouragement and love in the completion of my thesis, I am absolutely grateful.

Thank you all.

ABSTRACT

In this study, DC-DC boost converter Matlab Simulink Package has been developed and tested for the enhancement of learning process within academic course of power electronics. Respondent for this research were chosen randomly from Faculty of Electrical & Electronic Engineering, Tun Hussein Onn University of Malaysia. Aim of this study is to figure out and see the effectiveness of DC-DC boost convertors Simulink package for the enhancement of learning process of Power electronic course. A Pre-research statistical analysis based on the response of concerned students acquired through a relative questioner is employed to affirm the need of this simulation package. Analysis for this study has been verified by using Statistical Package for Social Science (SPSS) Version 20.0 software. Afterwards, a simulation package as required has been developed accordingly to test and illustrate the operation of DC-DC boost convertor using open-loop, Proportional integral derivative (PID) controller and Fuzzy logic controller topologies. Finally, a post-research questioner was also floated through same respondent population in order to evaluate and assess the effect and significance of the designed simulation package. It was observed through the statistical analysis of the afore mentioned post research questioner that, the use of simulation based package regarding the enhancement of learning proved to have a significant effect. Expect this study findings will be one of the catalysts in strengthening improve the instructional methods by using simulation software's in Power electronics and engineering courses.

ABSTRAK

Dalam kajian ini, DC-DC boost converter Matlab Simulink Package telah dibangunkan dan diuji untuk peningkatan proses pembelajaran dalam mata pelajaran kuasa elektronik. Responden bagi kajian ini telah dipilih secara rawak dari Fakulti Kejuruteraan Elektrik & Elektronik Kejuruteraan, Tun Hussein Onn Universiti Malaysia. Tujuan kajian ini adalah untuk mengetahui dan melihat keberkesanan DC-DC boost converter Matlab Simulink Package untuk menambahbaik proses pembelajaran mata pelajaran elektronik kuasa. Ujian sebelum (pre-research) untuk analisis statistik berdasarkan maklumbalas pelajar diperolehi melalui soal selidik untuk mengesahkan keperluan pakej simulasi ini. Di dalam kajian ini, penyelidik menggunakan perisian Statistical Package for Social Science (SPSS) versi 20.0. Selepas itu, pakej simulasi seperti yang dikehendaki telah dibangunkan dengan sewajarnya untuk menguji dan menggambarkan operasi DC-DC penukar rangsangan menggunakan open-loop, Proportional integral derivative (PID) controller dan Fuzzy logic controller topologies. Akhir sekali, ujian selepas (post-research) diapungkan melalui maklum balas responden untuk menilai dan menguji keberkesanan pakej simulasi yang direka. Melalui analisis statistik yang dilakukan dalam ujian selepas (post-research), penggunaan pakej simulasi mengenai peningkatan pembelajaran terbukti mempunyai kesan yang ketara. Diharapkan dapatan kajian ini akan menjadi salah satu pemangkin dalam meningkatkan kaedah pengajaran dengan menggunakan perisian simulasi ini dalam mata pelajaran kuasa elektronik dan bidang kejuruteraan.

TABLE OF CONTENTS

CHAPTER	CONTENT	PAGE
	TITLE	i
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	TABLE OF CONTENT	vii
	LIST OF FIGURES	xii
	LIST OF TABLE	xiv
	LIST OF ABBREVIATION	xvi
	LIST OF APPENDICES	xviii

CHAPTER 1 INTRODUCTION

1.1	Introduction	1
1.2	Problem Statement	3
1.3	Objective	5
1.4	Hypothesis	6
1.5	Importance of Study	6
1.6	Study Scope	7
	1.6.1 Simulation Scopes on Matlab Package	7
1.7	Study Restriction	8
1.8	ADDIE Model Of Instructional Design	8

1.9	Different Learning Styles	10
-----	---------------------------	----

CHAPTER 2 LITERATURE REVIEW

2.1	Introduction	13
2.2	Simulation-Based Learning	15
2.3	Pedagogical Philosophy	16
2.3.1	Pedagogical Approach	16
2.4	Matlab simulation based learning	17
2.4.1	Matlab Simulink for Power Electronics	18
2.5	DC-DC Converters	19
2.5.1	Non Isolated DC-DC Converters	19
2.5.1.1	Buck converter	19
2.5.1.2	Boost Converter	20
2.5.1.3	Buck-Boost Converter	21
2.5.1.4	Cuk Converter	21
2.5.2	Isolated DC-DC Converters	22
2.5.2.1	Fly Back Converter	22
2.5.2.2	Forward converter	23
2.5.2.3	Functions of DC-DC converters	24
2.6	DC-DC converter switching	25
2.7	Advantages of DCM	28
2.8	Disadvantages of DCM	29
2.9	Boost Converter	29
2.9.1	Analysis for switch closed (<i>on</i>)	31
2.9.2	Analyses for switch open (<i>off</i>)	32
2.10	PID Controller	36
2.11	Fuzzy logic controller system	38
2.12	Fuzzification	40
2.13	Advantages of Fuzzy Logic Controller	45

CHAPTER 3 METHODOLOGY

3.1	Introduction	46
3.2	Flow chart for Design Study and Methodology	48
3.3	Sampling	49
3.4	Study Instruments	49
3.5	Pre-Research Questioner	49
3.6	Post-Research Questioner	51
3.7	Boost Convertor Parameters	52
3.8	Fuzzy Logic Controller and Its Operational Methodology	53
3.9	Rule Base	55
3.10	Data Analysis Procedure For Pre-Research	56
	3.10.1 Respondent Based On Gender	56
	3.10.2 Student Response On Pre-Research Questions	57
	3.10.3 Analysis Results Of Pre-Research Questioner	60
3.11	Reliability and Validity Analysis	61
3.12	Data Analysis Method For Post-Research Questioner	64
3.13	Conclusion	66

CHAPTER 4 RESULTS AND ANALYSIS

4.1	Introduction	67
4.2	Results And Findings	69
4.3	Objective 1: Development of Matlab Simulink Package.	69
	4.3.1 Analyze Phase	70

4.3.2	Design Phase	70
4.3.3	Development Phase	71
4.3.4	Implementation and Evaluation Phase	73
4.4	Objective 2: Investigate The Voltage Outputs	74
4.4.1	Analysis For Open Loop Boost Convertor	74
4.4.2	Analysis For Boost Convertor with PID	76
4.4.3	Analysis For Boost Convertor with Fuzzy	77
4.5	Objective 3: Comparison Between Outputs	80
4.6	Data Analysis Post-Research Questioner Section A	81
4.6.1	Data Analysis Based On Gender	82
4.6.2	Data Analysis Based On CGPA	83
4.6.3	Data Analysis Based On Education	84
4.6.4	Data Analysis Based On Learning Style	85
4.7	Data Analysis Post-Research Questioner Section B	86
4.7.1	Data Analysis Of Objective 4	87
4.7.2	Data Analysis Of Objective 5	88
4.7.3	Data Analysis Of Objective 6	89
4.7.4	Data Analysis Of Objective 7	90
4.8	Results Of Overall Mean and Standard Deviation	92
4.9	Hypothesis Analysis	93
4.9.1	Hypothesis	93
4.9.2	Coefficient Of Determination In Multiple Regression.	94
4.10	Comment Section Description	96
4.11	Conclusion	96

CHAPTER 5 DISCUSSION, CONCLUSION AND RECOMMENDATIONS

5.1	Introduction	97
5.2	Discussion	98
5.2.1	Respondent Background	98
5.2.2	Ramification Of Matlab Simulink Package	98
5.2.3	Learning From Matlab Simulink Package	99
5.2.4	Response From Matlab Simulink Package	101
5.2.5	Benefits Of Matlab Simulink Package	102
5.3	Analysis Indication	103
5.4	Conclusion	104
5.5	Recommendations	105
5.5.1	Recommendation For UTHM	105
5.5.2	Recommendation For Further Research	106

REFERENCES	107
-------------------	-----

APPENDICES	109
-------------------	-----

LIST OF FIGURES

NO	Title	Page
1.1	ADDIE Model	9
2.1	The Basic Circuit Configuration of the Buck Converter	20
2.2	Basic Circuit of Boost Converter	20
2.3	Basic Circuit of Buck-Boost Converter	21
2.4	Basic Circuit of Cuk Converter	22
2.5	Basic Circuit of Fly-Back Converter	23
2.6	Basic Circuit of Forward Converter	24
2.7	Switching ON and OFF of DC-DC converter	26
2.8	T_{ON} and T_{OFF} pulse	26
2.9	Continuous Conduction Mode	27
2.10	Discontinuous Conduction Mode	27
2.11	i_L and V_L when inductor looks like short circuit	28
2.12	A Boost Converter Circuit	30
2.13	The Duty Cycle for Switching Period during Steady State	30
2.14	The Equivalent Circuit of Boost Converter When the Switch S Is Closed	31
2.15	Analysis for Switch Closed (<i>on</i>)	32
2.16	The Equivalent Circuit of Boost Converter When the Switch S Open	33
2.17	Analysis for Switch Opened (Off)	33

2.1 8	Control Methods for DC-DC Converters	36
2.19	Proportional-Integral-Derivative (PID) Controllers	37
2.20	Fuzzy Logic Controller Schematic	39
2.21	FLC Overall Structure	39
2.22	The Features of A Membership Function	40
2.23	(A) Triangular Membership Function Shape	42
2.23	(B) Gaussian Membership Function Shape	42
2.23	(C) Trapezoidal Membership Function Shape	42
2.23	(D) Generalized Bell Membership Function Shape	45
2.23	(E) Sigmoidal Membership Function Shape	48
2.24	Weight Average Method Defuzzification	54
3.1	The Overview of the Methodology Flow Chart of this Project.	72
3.2	Block Diagram of Fuzzy Control System	72
4.3.3	(A) Screen Shot Of Open Loop	72
4.3.3	(B) Screen Shot Of PID	73
4.3.3	(C) Screen Shot Of Fuzzy Logic	73
4.6.1	Sprinkling Of Respondents Based On Gender	82
4.6.2	Sprinkling Of Respondents Based On CGPA	83
4.6.3	Sprinkling Of Respondents Based On Education	84
4.6.4	Sprinkling Of Respondents Based On Learning Style	85

LIST OF TABLES

NO	Title	Page
2.1	Example of rule base	42
3.1	The value of all parameters can be determined as below	43
	Parameters and values for boost converter	
3.10.2	Questions Analysis of Pre-Rsearch Questions	57
	(a),(b),(c),(d),(e),(f),(g)	
3.11	Alpha Cronbach Level Of Reliability	61
3.11.1	Results From Validity Reliability	62
3.11.2	SPSS Reliability Analysis	63
3.12	Data Analysis Method	64
4.5	(A) The Features of A Membership Function	80
4.5	(B) Voltage Results From Open Loop	81
4.6.1	Sprinkling Of Respondents Based On Gender	82
4.6.2	Sprinkling Of Respondents Based On CGPA	83
4.6.3	Sprinkling Of Respondents Based On Education	84
4.6.4	Sprinkling Of Respondents Based On Learning Style	85
4.7	Ladell Mean Level	86
4.7.1	Objective 4	87
4.7.2	Objective 5	88
4.7.3	Objective 6	90
4.7.4	Objective 7	91
4.8	Overall Mean	92

4.9.2 Coefficient of determination Results

94



LIST OF SYMBOLS AND ABBREVIATIONS

μ_e - Degree of membership function of error

Δ_e - Degree of membership function of delta of error

u - Degree of membership function of voltage output

\vee - Maximum operator

O - Output of COG

\wedge - Minimum operator

B - Bisector of Area

C - Capacitor

CCM - Continuous Conduction Mode

che - Change of Error

COG - Centroid of Gravity

D - Duty Cycle

DC - Direct Current

DCM - Discontinuous Conduction Mode

e - Error

FLC - Fuzzy Logic Controller

F_s - Frequency Switching

FKEE – Faculty of electrical and electronics engineering.

gaussmf - Gaussian Membership Function

KD - Derivative gain

KI - Integral gain

KP - Proportional gain

L - Inductor

MF - Membership Function

MOM - Mean of Maximum

MOSFET - Metal–Oxide–Semiconductor Field-Effect Transistor

NB - Negative Big

NS - Negative Small

PB - Positive Big

PID - Proportional Integral Derivative

PS - Positive Small

PWM - Pulse Width Modulation

R - Resistor

S – Switch

UTHM- University Tun Hussein onn Malaysia

VC -Voltage (Calculation)

Vo -Output Voltage

s -Kth - switching cycle Input Voltage

Vref- Reference output

ZE – Zero

UTHM-Universiti Tun Hussein Onn Malaysia

LIST OF APPENDICES

Appendix	Title	Page
Appendix A	Pre-Research Questionnaire Post-Research Questionnaire	109
Appendix B	Statistical Analysis Data	120
Appendix C	Supporting Documents	134




PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

CHAPTER I

INTRODUCTION

1.1 Introduction



Power electronics is, by nature, a multi-disciplinary subject, and for any instructor a challenging course to teach. It is especially demanding course because of variety of topics, such as circuit analysis, signals and systems analysis, and control theory. It is a combination of hands-on experience and solid knowledge of theory provides an active learning environment that leads to successful learning and understanding process.

The use of simulation has always been a powerful tool for technology in all its various fields of application. Power Electronics course is essential for electrical and electronics engineers and it is included in the undergraduate and Postgraduate syllabus. An effective power electronics laboratory is expected to combine theoretical and experimental aspects of the topics by using state-of-the-art software/hardware tools. Sometime during experiment students face many problems in understanding of the procedure of experiment. For them simulation based demonstration of experiment is very useful especially in power electronic and some relevant courses.

DC to DC boost converters are important in portable electronic devices such as cellular phones and laptop computers, which are supplied with power from batteries primarily. Such electronic devices often contain several sub-circuits, each with its own voltage level requirement different from that supplied by the battery or an external supply (sometimes higher or lower than the supply voltage) and boost converter (step-up converter) is a DC-DC power converter with an output voltage greater than its input voltage. They provide smooth acceleration control, high efficiency, and fast dynamic response. DC converter can be used in regenerative braking of DC motor to return energy back into the supply, and this feature results in energy saving for transportation system with frequent stop; and also are used, in DC voltage regulation (Rashid, 2004). In many ways, a DC-DC converter is the DC equivalent of a transformer. There are four main types of converter usually called the buck, boost, buck-boost and Boost converters. The main feature of a fuzzy controller is that it can convert the linguistic control rules based on expert knowledge into automatic control strategy. So it can be applied to control systems with unknown or un modeled dynamics. (Ozdemir, 1997)

Mostly, the DC-DC converter consists of the power semiconductor devices which are operated as electronic switches and classified as switched-mode DC-DC converters. Operation of the switching devices causes the inherently nonlinear characteristic of the DC-DC converters. Due to this unwanted nonlinear characteristics, the converters requires a controller with a high degree of dynamic response. Pulse Width Modulation (PWM) is the most frequently consider method among the various switching control method (J. Alvarez-Ramirez, Jan. 2001). In DC-DC voltage regulators, it is important to supply a constant output voltage, regardless of disturbances on the input voltage.

Currently, the control systems for many power electronic appliances have been increasing widely. Crucial with these demands, many researchers or designers have been struggling to find the most economic and reliable controller to meet these demands. The idea to have a control system in dc-dc converter is to ensure desired voltage output can be produced efficiently as compared to open loop system.

The focus of this research is the development of DC-DC boost convertor Matlab simulink package by using fuzzy logic controller for enhancing the learning process of power electronic course. In this project, Matlab simulink package is used as a platform for students to understand the function of DC-DC boost convertor. After the development of Boost convertor Matlab Simulink will be test on UTHM, Faculty of electrical and electronics engineering students and then evaluate and analyze the effectiveness of this Matlab simulink package with the help of design Post-research questioner which will discuss in chapter 4 of this study.

1.2 Problem Statement

Power electronics is one of the essential course in engineering (electrical and electronics), and the main focus of this course on diploma and degree level on DC-DC boost convertors. DC-DC boost convertors are widely used in industrial applications according to the requirement of project. Firstly, most of the power electronics final year degree students of Electrical engineering they are facing problems during working on hardware without testing on simulation based software, that's why they waste a lot of their money and time and sometimes they may damage expensive laboratory equipment's of university and Polytechnics because they are working on hardware without any precaution and proper handling.

Secondly most of the students have different learning styles like auditory, visual and hands-on. Sometimes student they cannot understand on first attempt and sometimes because of improper material used in class might be the reason why students can't perform well in exams. Students also might feel annoyed with the material used which will lead them to lose concentration and attention in the class. Many students they prefer visual and hands-on learning style rather than auditory or teacher center. For these type of students simulation based software's are very useful and especially in electrical and electronics engineering students with the help of this simulation based software they can

repeat and redo their required experiment before working on hardware even the last year students of faculty of Faculty of Electrical and Electronic, UTHM are facing same problem in their experimental work which is analyzed from Pre-Research Questioner data of this research for the justification of this problem statement.

For enhancing the learning process of power electronics course, experimental work before working on hardware its better and effective to implement DC-DC convertor on Matlab simulink for sufficient learning outcome and also save costly electrical equipment. Developing the fuzzy controller is cheaper than developing a model based or other controllers for the same purpose. Proportional-Integral- Differential (PID) controllers have been usually applied to the converters because of their simplicity. However, the main drawback of PID controller is unable to adapt and approach the best performance when applied to nonlinear system. It will suffer from dynamic response, produces overshoot, longer rise time and settling time which in turn will influence the output voltage regulation of the Boost converter.

The implementation of practical Fuzzy Logic controller that will deal to the issue must be investigated. The Fuzzy control is a practical alternative for a variety of challenging control applications because Fuzzy logic control is nonlinear and adaptive in nature that gives it a robust performance under parameter variation and load disturbances. Fuzzy controllers are more robust than PID controllers because they can cover wider range of operating conditions than PID, and can also operate with noise and disturbance of different natures. Fuzzy logic is suited to low-cost implementations and systems of fuzzy can be easily upgraded by adding new rules to improve performance or add new features.

1.3 Objective

The objectives of this project are,

- i. To develop a DC- DC Boost convertor Matlab Simulink package to enhance learning process of power electronics course.
- ii. To investigate the voltage output for DC-DC Boost converter between open loop, PID controller and fuzzy logic controller through Matlab simulink package.
- iii. To compare the output of close loop and open loop DC-DC boost convertor.
- iv. To identify the ramifications of Boost convertor Matlab Simulink software package.
- v. To analyze the Learning outcomes from Boost convertor Matlab Simulink software package.
- vi. To analyze the response from Boost convertor Matlab Simulink software package.
- vii. To identify the benefits of Boost convertor Matlab Simulink software package.

1.4 Hypothesis

H_0 : There is no significant change in the mean value of learning process of DC DC boost convertors by using Matlab simulink package.

1.5 Importance of Study

- i. To provide experience and the importance of simulation based power electronic course for final year degree student of electrical engineering.
- ii. Students will directly involve in this study and they are final year degree students from Faculty of Electrical and Electronic Engineering (FKEE), UTHM.
- iii. After the successful completion of this study, it might help various aspects. It can be used in Electrical Engineering Faculty (FKEE) and other Faculties for enhancing student's simulation based engineering skills.

1.6 Study Scope

The scopes of this project is to simulate the proposed method of voltage tracking of DC-DC boost converter using Fuzzy controller with Matlab Simulink software for the enhancement of learning process of power electronic students. Analyses of the converter will be done for continuous current mode (CCM) only. The analysis only covered the output voltage based on reading on overshoot ratio, rise time, peak time and settling time. In this project, Matlab simulink package is used as a platform in designing the fuzzy logic controller. This Matlab simulink package is develop to study the dynamic behavior of DC-DC boost converters and performance of proposed controller for the enhancement of learning process of Power electronics students.

1.6.1 Simulation Scopes Of Matlab Simulink

Simulation consists of:

- a) Modeling DC to DC converter.
- b) Modeling fuzzy logic controller.

REFERENCES

Ashfaq Ahmed, 1999, *Power Electronics for Technology*, page(s): 269-303.

Daniel W.Hart, 1997, *Introduction to Power Electronics*, page(s):185-204.

Guanrong Chen, Trung Tat Pham, 2001, Introduction to Fuzzy Sets, Fuzzy logic, and Fuzzy Control Systems.

Muhammad H. Rashid, Second Edition, *Power Electronics Circuit, Devices, and Applications*, page(s) :303-323.

GuangFeng, Wangfeng Zhang, Yan-FeiLui, *An Adaptive current Mode fuzzy Logic Controller for Dc to Dc Converter*, Applied Power Electronics Conference and Exposition, 2003, APEC '03.Eigtheenth Annual IEEE,9-13 Feb,2003, vol.2,page(s): 983-989.

Mattavelli, L.Rossetto, G.Spiazzi and P.Tenti, *General-Purpose Fuzzy Controller for DC-Dc Converter*, Proceedings of 1997, IEEE Transactions On Power Electronics, 1 January 1997, vol.12, no.1.

L.A Zedah, outline of new approach of the analysis of complex system and decision processes, 1963, IEEE Transactions System, Man, Cybern., vol. SMC-3, no.1, page(s):146-151.

Yonis Buswig , Yonis, Mohammed (2011). *Development of a DC-AC power conditioner for wind generator by using neural network*. Masters thesis, Universiti Tun Hussein Onn Malaysia.

W.M.Utomo, A. B. (April 2011). *Online Learning Neural Network Control of Buck-Boost Converter*. Eighth International Conference on Information Technology: New Generations (ITNG).

Ismail, N. I., Baharom, R., & Johari, D. (2010). Fuzzy logic controller on DC/DC boost converter. *Power and Energy (PECon), 2010 IEEE International Conference* . Kuala Lumpur.

Jantzen, J. (2007). *Foundations of Fuzzy Control*. West Sussex PO19 8SQ, England: John Wiley & Sons Ltd.

Adel E. El-kholy and A. M. Dabroom, (2006): *Adaptive Fuzzy Logic Controllers for DC Drives: A Survey of the State of the art*, Journal of Electrical Systems, pp. 116-145.

J.-S. Roger Jang, (1997): *Fuzzy Logic Toolbox User's Guide* COPYRIGHT 1984 - 1997 by The MathWorks, Inc. All Rights Reserved Cheng- Yuan Liou and Yen-Ting Kuo.

Collofello, J.S., et al. Using Software Process Simulation to Assist Software Development Organizations in Making Good Enough Quality Decisions. Summer Computer Simulation Conference, 1998 (SCSC98).

Hartmut Bossel, Modeling and simulation, A. K. Peters, Ltd., Natick, MA, 1994.